

3006890.50-QUA/EMC

EMC Test report for MR16 LED bulb Model 50-32MR

Hong Kong, date of issue: 2011-03-10

Author C.S. Man

By order of Matrix Lighting Limited at Hong Kong, China

author : C.S. Man

20 pages 0 annexes

(sec)

DEKRA Certification Hong Kong Ltd.

reviewed : Jimmy Woo

HK-F-PC4-005 r2.0



-page 2 of 20-

3006890.50-QUA/EMC

CONTENTS

		page
1	Conclusion	3
1.1	Model description	3
1.2	Environment	4
2	Summary	5
2.1	Applied standards	5
2.2	Overview of results	5
3	General Information	6
3.1	Product Information	6
3.2	Client Information	6
3.3	Test data	7
3.4	Environmental conditions	7
4	Emission test results	8
4.1	Mains conducted disturbance voltage	8
4.2	Radiated EM Field emission	10
4.3	Radiated Magnetic Field emission	11
4.4	Harmonic currents	12
4.5	Voltage fluctuations (Flicker)	13
5	Immunity Test Results	14
5.1	Electrostatic discharge immunity	14
5.2	Radiated EM field immunity	15
5.3	Electrical Fast Transient immunity	16
5.4	Surge transient immunity	17
5.5	RF Conducted immunity	18
5.6	Power supply interruptions and dips	19
6	Identification of the equipment under test	20

1 **CONCLUSION**

The equipment under test (EUT) meets the essential requirements of the EMC Directive 2004/108/EC.

The EUT is tested with a linear adaptor model WX48-25-93 which is provided by manufacturer.

The conclusion and results stated in this test report are based on a non-recurrent examination of sample(s) provided by the applicant.

1.1 Model description

The apparatus as supplied for the test is a MR16 LED bulb, model 50-32MR for residential use and the product is a LED bulb with build-in electronic driver.



Figure 1 model 50-32MR

The operating modes as stated in the user manual are on mode and off mode.